




Weather exposed wood surfaces can be protected from UV light, rain and fungus by **ULTRAN LASUR SERIES**. It's designed with water repellent and permeable ability.

Water repellent works to protect wood from water from the outside meanwhile, permeable ability allows water from the inside of wood to diffused and evaporase through the layer surface.

This ability stabilize water level on the wood. It keeps wood in a dry condition, protected from fungus and maintain the stability of wood.



Picture on the left shows the function of UV absorber, it reflects sun light and permeable ability which allows water to be diffused.



B picture shows water repellent's function, it protect wood from water outside.



www.propanraya.com



@propanraya



08111 381 686



ULTRAN LASUR SERIES

DURABLE EXTERIOR
WOOD AND DECK COATINGS





ULTRAN LASUR[®]

DEEP PENETRATING EXTERIOR LASUR

ULTRAN LASUR EL-501 is a wood care product that has strong penetration through wooden pores, especially designed for tropical weather. Suitable for prestigious projects, hotels, resorts and wood houses.

ULTRAN LASUR EL-501 is very recommended for exterior or interior usage, especially wooden parts that exposed intensively by extreme weather such as door, window, gazebo or park bench.

ADVANTAGES

- Good penetration through wood
- Water repellent and Permeable (allows water to 'breathe')
- UV Resistant
- No brush mark



DECK LASUR[®]

DURABLE EXTERIOR WOODEN FLOOR COATING

ULTRAN DECK LASUR EDL-601 is a variant from ULTRAN LASUR, designed for wooden deck and wooden floor. It can penetrate through wooden pores to increase the wood dimension's stability.

ADVANTAGES

- Weather and abrasion resistant
- Fungus resistant
- Flexible
- No brush mark



APPLICATION STEP :



ULTRAN LASUR[®]

DEEP PENETRATING EXTERIOR LASUR

1. Sand along the wood grain with sandpaper number 180 and make sure the surface is free from dust and dirt.
2. Apply Ultran Lasur with brush and let 6 – 8 hours to dry. Sand lightly with sandpaper number 400. Repeat this step three times for optimum result.
3. For gloss/dof appearance, apply Ultran Lasur Natural gloss/dof for final top coat.



DECK LASUR[®]

DURABLE EXTERIOR WOODEN FLOOR COATING

1. Sand along the wood grain with sandpaper number 180 and make sure the surface is free from dust and dirt.
2. Apply Ultran Deck Lasur with brush and let 6 – 8 hours to dry. Sand lightly with sandpaper number 400. Repeat this step three times for optimum result.
3. For satin appearance, apply Ultran Deck Lasur Natural satin for final top coat.

Tips :

- Do not apply wood filler to fill the pore for exterior uses, because the weather resistant and adhesion of Ultran Lasur or Ultran Deck Lasur on the wood substrate will be affected.



LASER
COLOR

- Brighter Color
- Odorless
- Weather Resistant

ALSO AVAILABLE!
Color variants from

LASUR LASER