

DECOFLOOR

DECORATIVE, SLIP RESISTANT
CONCRETE COATING

DECOFLOOR

DECOFLOOR is 1 component acrylic waterbased decorative coating, that can be applied as floor and wall coating. DECOFLOOR is specially formulated for several substrates, such as: concrete, natural stone and other substrate with prorus surface, and can be applied both for interior and exterior. DECOFLOOR offers unique dot appearance and can be applied for garage, walking pavement, driveways and balcony. **DECOFLOOR** has a very good penetration to hair crack concrete and resistance to tire marks, oil, dirt and household stain.

Substrate:

- Concrete
- Natural Stone
- Bricks
- Other substrate with porous substrate

Application Area:

- Garage
- Walking pavement
- Driveways
- Balcony

**1 Beautify
The Concrete**

Granite stone appearance

**2 Durable
Color**

Not easy to fade

**3 Excellent
adhesion
on concrete**

Not easy to peel off

**4 Weather
Resistance**


For exterior & interior

**5 Easy
To Apply**

Fast application time


**6 Water
Based**

Environmental friendly



Diamond Grey

9492



Granite Grey

9491



Aurora Clay

3448



Carnival Brown

3447



Mountain Blue

6454



Victoria Green

8419

APPLICATION PROCEDURE




1 Mix well Concrete Floor Wash with water (ratio 1 : 1).



4 Mix Decofloor flake to Decofloor Basic Coat and mix well, without any thinner.

Pour Decofloor to the roller tray.



2 Use Concrete Floor Wash to clean and open the substrate pores.



5 Apply DECOFLOOR by using mohair roll to all concrete substrate, let dry at least 3 - 4 hours.



3 Brush concrete surface and rinse with clean water to clean the remains of Concrete Floor Wash. Let dry for 24 hours before applying DECOFLOOR.



6 Apply DECOFLOOR 1 more time without thinner and let dry. Let it dry completely, at least 3 days, before substrate ready to use.

MIXING :



**DECOFLOOR
Basic Coat
3 kg**



**DECOFLOOR
Flake*
1 kg**

* Flake packaging is separated.

Type	Acrylic water based
Color	See colorcard
Specific gravity	1,27 g/cc
Application method	Roll mohair
Thinner	-
Packaging	4 kg-set
Re-coating time	3 - 4 hours (30° C)
Coverage	1 - 2 m²/kg (1 coat)